

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
28 July 2005 (28.07.2005)

PCT

(10) International Publication Number  
**WO 2005/067752 A1**

(51) International Patent Classification<sup>7</sup>: **A42B 3/12**

[KR/KR]; 187, Songmun-ri, Yangji-myeon, Yongin-si,  
Gyeonggi-do 449-823 (KR).

(21) International Application Number:  
PCT/KR2004/001409

(74) Agent: **YOUN, Kyu-Cheol**; New-Tech International  
Patent & Law Office, 10th Floor, Teheran Building,  
825-33 Yeoksam-dong, Kangnam-ku, Seoul 135-080  
(KR).

(22) International Filing Date: 14 June 2004 (14.06.2004)

(25) Filing Language: Korean

(26) Publication Language: English

(30) Priority Data:  
10-2004-0002573 14 January 2004 (14.01.2004) KR

(71) Applicant (for all designated States except US): **SAN-  
CHEONG CO., LTD.** [KR/KR]; 185, Songmun-ri,  
Yangji-myeon, Yongin-si, Gyeonggi-do 449-823 (KR).

(72) Inventor; and


(75) Inventor/Applicant (for US only): **KIM, Jong-Kee**

(81) Designated States (unless otherwise indicated, for every  
kind of national protection available): AE, AG, AL, AM,  
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,  
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,  
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,  
KG, KP, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG,  
MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH,  
PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN,  
TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every  
kind of regional protection available): ARIPO (BW, GH,  
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,

[Continued on next page]

(54) Title: **INNER SHELL FOR SAFETY HELMETS AND METHOD OF PRODUCING THE SAME**



(57) Abstract: Disclosed is an inner shell for safety helmets, which is massproduced and has a structure capable of efficiently absorbing and dispersing an impact, and a method of producing the same, which ensures the reduced material costs and the improved workability and productivity. The inner shell (10) includes a liner member (12) having openings at upper and lower parts thereof, and an impact absorbing member (14) surrounding a circumference of the liner member (12). The method includes injection-molding a molten plastic resin into a predetermined shape of liner member (12), putting the molded liner member (12) in a metal mold, forming the impact absorbing member (14) using a foamed resin, including Styrofoam, a polyethylene foam, and a urethane foam, in the metal mold after the metal mold is hermetically sealed, separating the inner shell (10) from the metal mold, and finishing the inner shell (10).

WO 2005/067752 A1



ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),  
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,  
FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,  
SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,  
GW, ML, MR, NE, SN, TD, TG).

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

**Published:**

— with international search report